



COLLAPSIBLE CONTAINMENT TANK

The self-supporting containment tank is designed to be used as a utility water reservoir or a collection tank for hazardous substances. Due to its rapid assembly and light weight the tank is suitable for pumping liquids from accidental spillages or as a backup water reservoir at difficult to reach areas. The most in demand hexagonal tanks are in volumes of 1000 and 2000 litres.



The tanks are made of highly resistant PES/ PVC coated material with textile reinforcement. The sidewalls have 6 mm thick polypropylene reinforcements welded inside.



The temperature range of use is from -30°C to +70°C.




The material is resistant against chemical and oil substances, thereby providing enhanced potential of use in environmental accidents.



↑
The tank can be packaged to surprisingly small dimensions



↑
The whole tank can be erected by a single person in minutes



↑
After erecting the hexagonal tarp is fixed with special fastening hooks

It is necessary for the tank to be placed on an even surface, without any sharp object. It is recommended to place the tank on a protective pad to increase its lifetime.

Specifications

	1000	2000
Volume (l)	1000	2000
Diameter inside/outside (mm)	1300 / 1500	1380 / 1600
Height (mm)	700	800
Sidewall width (mm)	750	1000
Weight (kg)	30	50
Pack Size (mm)	800 x 750 x 100	1050 x 850 x 100

Distributor



Aggeres nv
Boomgaardreef 9
2900 Schoten
Belgium

Tel.: +32 (0)3 633.15.50
Fax: +32 (0)3 633.22.50
info@aggeres.com
www.aggeres.com